



Package



61*53*26CM/8PCS

| LED Wattage | Product Weight |
|-------------|----------------|
| 30W | 1.5 KG |
| 45W | 1.5 KG |
| 60W | 1.5 KG |
| 65W-HV | 1.5 KG |

- Replaces conventional Halogen lamps
- SUNON FANS
- Durable chip and fade resistant powder coat finish
- MEAN WELL Dimmable Driver HLG Series
- Patent LED protector
- Installation plate free to design
- High Lumens output
- High Quality LED's
- Cast aluminum thermal management for optimal heat sinking
- 5 years warranty



| | RL-RTK-30W-LV-D | RL-RTK-45W-LV-D | RL-RTK-60W-LV-D | RL-RTK-65W-HV-D |
|------------------------------|-------------------|-------------------|-------------------|-------------------|
| INPUT WATTS | 30W | 45W | 60W | 65W |
| DELIVERED LUMENS(lm) | 2956.1 lm | 4675.3 lm | 6755.8 lm | 7203.8 lm |
| L70 Life (Hours) | 60600 hours | 60600 hours | 60600 hours | 69600 hours |
| EFFICACY (lm/W) | 112.91 lm/W | 114.42 lm/W | 111.43 lm/W | 107.95 lm/W |
| COLOUR TEMP | 5783 k | 5821 k | 5856 k | 5944 k |
| EQUIVALENT WATTAGE | 80W MH | 90W MH | 120W MH | 130W MH |
| POWER FACTOR | 0.9857 | 0.9952 | 0.9951 | 0.9919 |
| COLOUR RENDERING INDEX (CRI) | >70 | >70 | >70 | >70 |
| WORKING TEMPERATURE | -30° F to +130° F | -30° F to +130° F | -30° F to +130° F | -30° F to +130° F |
| INPUT VOLTAGE | AC100-277V | AC100-277V | AC100-277V | AC200-480V |

Model Profile: "XX" in model name can be "FL", "AL", "SB", "ST" or "WP" denotes series code for commercial use.
 "YY" in model name can be "SW", "WW", "NW", "DW" or "CW" denotes LED color temperature or color of LED.